DEVICE FOR ACTIVATING PERSONAL PROTECTION MEANS

FIELD OF THE INVENTION

The present invention is directed to a device for activating a
personal protection device.

5   BACKGROUND INFORMATION

German Patent Application No. DE 100 33 907 A1 describes a
device for activating a personal protection device, in which
the crash severity, for example, determined by a frontal
sensor, is used for activating the personal protection means.

10

SUMMARY

A device according to an example embodiment of the present
invention for activating a personal protection device may have
the advantage over the related art that the delay between a

15   first signal from an impact sensor system situated in the
front of the vehicle, which identifies an impact, and a second
signal from an acceleration sensor system located centrally in
the vehicle, which also indicates the impact is determined.
This delay provides information not only about the crash

20   sequence, but also about the crash partner. A parameter which
serves for improved activation of the personal protection
devices such as airbags, belt tensioners, rollover bars, or
pedestrian protection devices is thus available.

25   It may be particularly advantageous if the device determines a
crash severity as a function of the delay and activates the
personal protection device as a function of the crash
severity. The acceleration sensor installed centrally in the
vehicle, typically on the transmission tunnel, does not see

30   the direct impact with the object. Several milliseconds elapse
until an acceleration signal is detected. This time delay is a
function of the crash configuration, i.e., the impact velocity

SUBSTITUTE SPECIFICATION

and the relationship between the rigidities and masses of the accident partners. Determining this delay between impact and reaching a start threshold, i.e., the noise threshold and the analysis of the impact pulse following the start threshold,
5 allows accurate conclusions to be drawn about the crash severity.

The first and second signals are generated by the noise thresholds being exceeded due to an impact. The impact sensor
10 system may be contact switches in particular. They are closed by the effect of the impact.

It may be advantageous if the device starts a deployment algorithm as a function of the signal of the impact sensor
15 system. The deployment algorithm is synchronized to the actual time of impact. Synchronization to the actual impact allows simple differentiation of soft barriers, in particular in the lower velocity range.

20 It may also be particularly advantageous if the device determines a size of an impact object as a function of the delay and influences the deployment algorithm as a function of the size. This is possible in particular in the case of pole crashes. First of all, the deployment sensitivity, i.e., a
25 change in the noise threshold, may thus be achieved. There are only slight decelerations after the impact pulse due to the penetration of the pole into the soft vehicle structures. This does not change until after a later point in time, when the pole encounters massive structures such as the engine block,
30 for example, causing the vehicle to decelerate. Identification of the object results in adjustment of the deployment threshold.

It may also be advantageous if the device according to the
35 example embodiment of the present invention issues an estimate of the site of impact on the basis of the delay, the site of

SUBSTITUTE SPECIFICATION

impact being taken into account in activating the personal protection means.

The impact sensor system may advantageously have a contact
5   sensor system such as a force switch and/or an acceleration sensor system. These sensors my be situated directly on the bumper; however, they may also be situated in the extended vehicle front area such as on the front hood.

10   Finally, it may also be advantageous if the impact sensor system is distributed on the vehicle front to better detect the site of impact.

BRIEF DESCRIPTION OF THE DRAWINGS
15   Exemplary embodiments of the present invention are illustrated in the figures and explained in greater detail below.

Figure 1 shows a block diagram of a device according to an example embodiment of the present invention.
20

Figure 2 shows another block diagram of the device according to an example embodiment of the present invention.

Figure 3 shows another block diagram of the device according
25   to an example embodiment of the present invention.

Figure 4 shows a flow chart.

Figure 5 shows a signal comparison including the influence of
30   the noise threshold.

Figure 6 shows a signal comparison without the influence of the noise threshold.

35   Figure 7 shows an effect of the start threshold.

Figure 8 shows a pole crash.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

By law, pedestrian protection must be introduced in vehicles
within the European Union starting in 2005. In addition to
initial passive approaches such as appropriate design of the
vehicle front, active protective measures will be introduced
in later stages. These protective measures include airbags in
the area of the front hood and impact sensors whose signals
cause these airbags to be activated. Impact sensors may
include pre-impact sensors such as radar, ultrasound, and/or
contact sensors. The contact sensors indicate the direct
object impact and, depending on the measurement principle, may
contribute to the classification of the impact object.
Furthermore, the activation of airbags for occupant protection
should be even better adjusted to the situation. For this
purpose, further information is required.

According to an example embodiment of the present invention, a
delay between a signal of a contact sensor and that of a
centrally located acceleration sensor is used for improving
the activation of the personal protection device. The contact
sensor detects an impact at an early stage, while the
acceleration sensor system, due to its central position on the
transmission tunnel usually in the airbag control unit, does
not detect it before a few milliseconds have elapsed. The
delay may contribute valuable information for determining the
crash severity and crash type, for estimating the size of the
impact object, and estimating the site of impact.

Figure 1 shows a device according to the example embodiment of
the present invention in a first block diagram. A contact
sensor system 11 is situated in a vehicle 10 in the vehicle
front area. The contact sensor system may be situated in the
bumper in particular. It includes one or more switches or also
acceleration sensors. A signal line connects contact sensor

system 11 to a centrally situated control unit 12 for activating personal protection means. For example, control unit 12 is connected to personal protection means 13 and 14, which are to represent airbags here, via data outputs. Control
5   unit 12 is normally connected to a much larger number of personal protection devices; however, only two are illustrated here as an example. In addition to a processor, normally a microcontroller, for activating personal protection devices 13 and 14 and for analyzing the signals of contact sensor system
10   11, an acceleration sensor system, which is sensitive at least in the longitudinal direction of the vehicle, is also located in control unit 12. The signals of this acceleration sensor system are also analyzed by the processor of control unit 12. Control unit 12 then activates personal protection devices 13
15   and 14 as a function of these signals.

According to the example embodiment of the present invention, control unit 12 determines a delay between the signals of contact sensor system 11 and its own acceleration sensor
20   system 12. Contact sensor system 11, whose signal is transmitted over the signal line to control unit 12 almost without delay, detects an impact, for example, on the front of the vehicle, considerably earlier than centrally situated control unit 12 via its acceleration sensor. The crash
25   severity may be determined, the deployment algorithm in control unit 12 may be started in a timely manner, and the size of the impact object and the site of impact may be estimated on the basis of this delay. Contact sensor system 11 may be supplemented by additional sensors such as acceleration
30   sensors and pre-crash sensors. Additional sensors such as an occupant sensor system and other acceleration and/or pressure sensors are connected to control unit 12, but are not illustrated here for the sake of simplicity.

35   Figure 2 shows another block diagram of the device according to the example embodiment of the present invention. Contact

                                SUBSTITUTE SPECIFICATION

sensor system 20 is connected to an analyzer module 21, which processes the signal of contact sensor system 20 and transmits it via the signal line to control unit 22. Control unit 22 has a receiver module 23, which receives the signal from module 21

5   and transmits it to a processor 24 in control unit 22. Processor 24 also takes into account signals from acceleration sensor system 25 located in control unit 22. This acceleration sensor system 25 detects at least the acceleration in the longitudinal direction of the vehicle. Processor 24 activates

10   output stages 26, which are connected to an ignition circuit 27 for example, as a function of these acceleration signals and the signal from contact sensor system 20. In particular, processor 24 starts its deployment algorithm as a function of a signal from contact sensor system 20. Processor 24

15   determines, from the delay between the signal from contact sensor system 20 and acceleration sensor system 25, the crash severity, a size of the impact object, and the site of impact, in order to determine therefrom which personal protection devices are to be activated and how.

20

Figure 3 shows a special configuration of the contact sensor system. In front 30 of the vehicle, different sensors 30, 32, 33, and 34, normally switches, are distributed over the length of the vehicle front. These switches are connected to an

25   analyzer module 35, which processes these signals for transmission to control unit 22. This configuration allows a site of impact to be easily identified. The impact sensors on the vehicle front may also be arranged vertically above one another. A field of such impact sensors may thus also be

30   provided on the front of the vehicle.

Figure 4 explains, using a flow chart, the sequence executed by the device according to the example embodiment of the present invention. In method step 400, the signal is generated

35   by contact sensor system 20 and transmitted, via modules 21 and 23, to processor 24 of control unit 22. In method step

                                  SUBSTITUTE SPECIFICATION

401, the second signal is generated by acceleration sensor system 25. There is a delay between these two signals, which is determined in method step 402. On the basis of the delay, processor 24 determines the crash severity; in step 403 it

5   starts algorithm 404 as a function of the first signal and determines the size of the opposite party of the accident in method step 405. In addition, the impact point may be determined, on the basis of the delay and other signals, in step 406. Restraining devices 27 are then activated on the

10   basis of this information in step 407.

The upper diagram of Figure 5 shows accelerations for a frontal impact and for impacts against a soft and a hard barrier. The lower diagram of Figure 5 shows the corresponding

15   decrease in velocity. Synchronization to the actual impact allows simple differentiation of soft barriers, in particular in the lower velocity range. The airbag control unit continuously monitors the signals of sensor 25. If these signals exceed a first threshold (hereinafter noise

20   threshold), the processor starts analyzing the signals. This threshold may be established in different ways: as a simple threshold or, for example, by comparison of two window integrals having different lengths, which differ from one another in the event of a crash. The only important thing here

25   is the determination of the start point via the acceleration signals. The signals experience a certain delay due to the structure, because they usually travel from the bumper via the longitudinal structure to the sensor in the airbag control unit. This delay is also a function of the impact velocity and

30   the hardness of the barrier. Figure 5 shows three different configurations.

Signal 50: 55 km/h against a rigid barrier
Signal 51: 26 km/h against a rigid barrier

35   Signal 52: 15 km/h against a rigid barrier

These three different impact velocities are plotted in the
graph of acceleration and the resulting integrated change in
velocity. The similarities between the integral curves of
signals 51 and 52 are readily apparent. This results in
5   considerable complexity in differentiating these two different
crashes, because signal 52 is to be classified as a non-
deployer.

In Figure 6, the same signals are plotted again, however, with
10   synchronization from impact start. This is provided by impact
sensor 11. The signals now are:

Signal 60: 55 km/h against a rigid barrier
Signal 61: 26 km/h against a rigid barrier
15   Signal 62: 15 km/h against a rigid barrier

In the lower figure the three different signals are easily
differentiated visually. This is achieved via the information
of impact sensor 11.
20
Figure 7 shows the effect of a start threshold. Determining
this delay between impact and reaching a start threshold and
the analysis of the impact pulse following the start threshold
allows accurate conclusions to be drawn about the crash
25   severity.

Figure 7 shows that the impact pulse of the 64 km/h impact
against a deformable barrier differs from the 26 km/h crash
against a rigid barrier. However, in examining the decreased
30   velocity, the 26 km/h crash appears as a stronger signal even
after a short time. The 26 km/h crash is shown by curve 70 in
the acceleration-time diagram and the velocity decrease-time
diagram, while the 64 km/h crash is shown by curve 71.

35   Furthermore, Figure 7 shows vertical lines (4.5 ms, 8 ms,
19 ms); these marks are reached by the corresponding signals

                                        SUBSTITUTE SPECIFICATION

(71, 70, 72) via the threshold shown (~3 g). The time marks indicate the delay due to the structure and are roughly inversely proportional to the impact velocity (indicator only). Furthermore, the acceleration curve following the mark

5   (first peak) may be analyzed and information regarding the barrier hardness may be obtained. It is readily apparent that curve 71 produces a pronounced peak, which occurs earlier and has a considerably different shape from that of signal 70. Curve 72 is plotted as a reference. Similar information may

10   also be derived from Figure 8.

Figure 8 shows the effect of a pole crash via an acceleration-time diagram and a velocity decrease-time diagram. If the size of an impact object is detectable, this may be used for

15   changing the deployment sensibility in the event of pole crashes. There are only slight decelerations after the impact pulse due to the penetration of the pole into the soft vehicle structures. This does not change until after the 40 ms time mark, as shown by curve 81, when the pole encounters massive

20   structures such as the engine block, for example, causing the vehicle to decelerate. An identification of the object, the size of the impact, and the crash sequence may adjust the deployment threshold in this case.

SUBSTITUTE SPECIFICATION